


Air conditioners

Heating & Cooling

Siesta

- » **Stylish front panel**
- » **Silent operation**
- » **Vertical auto swing**
- » **Standard air filter**
- » **Anti-corrosion treated outdoor heat exchanger fin**
- » **SEER/SCOP:**
Up to 

Wall mounted unit



www.daikin.eu



ATXN-MB



Inverter



Fan only

Powerful
modeAuto cooling-
heating
changeoverIndoor
unit silent
operationComfortable
sleeping
modeVertical auto
swingAuto fan
speedFan speed
stepsDry
programme

Air filter



24 hour timer


Infrared
remote
control

Auto-restart



Self diagnosis

Heating & Cooling

INDOOR UNIT				ATXN25MB		ATXN35MB		ATXN50MB		ATXN60MB			
Cooling capacity	Min./Nom./Max.		kW	1.30/2.56/3.00		1.30/3.41/3.80		1.63/5.48/6.20		1.75/6.23/6.50			
Heating capacity	Min./Nom./Max.		kW	1.30/2.84/4.00		1.30/3.58/4.75		1.17/5.62/6.60		1.20/6.40/7.10			
Power input	Cooling	Nom.	kW	0.693		1.205		1.718		1.931			
	Heating	Nom.	kW	0.700		0.950		1.500		1.680			
<div></div> Seasonal efficiency (according to EN14825)	Cooling	Energy label				A+				A			
		Pdesign		kW	2.56		3.41		5.48		6.23		
		SEER					5.61				5.15		
		Annual energy consumption		kWh	160		213		342		423		
	Heating (Average climate)	Energy label						A					
		Pdesign		kW	2.51		2.58		3.64		3.80		
		SCOP			3.81				3.99		3.81		
		Annual energy consumption		kWh	922		948		1,277		1,396		
Casing	Colour			White									
Dimensions	Unit	HeightxWidthxDepth	mm	288x800x206				310x1,065x224					
Weight	Unit		kg	9				14					
Fan-Air flow rate	Cooling	Super high/High/Nom./Low/Silent operation	m ³ /min	10.68/9.78/7.68/6.06/4.68		11.10/10.14/7.98/6.54/4.68		16.38/15.00/13.32/11.82/10.62		19.92/18.54/16.56/14.34/12.36			
	Heating	Super high/High/Nom./Low/Silent operation	m ³ /min	10.68/9.78/7.68/6.06/4.68		11.10/10.14/7.98/6.54/4.68		16.38/15.00/13.32/11.82/10.62		19.92/18.54/16.56/14.34/12.36			
Sound power level	Cooling		dBA	53		54		55		61			
Sound pressure level	Cooling	Super high/High/Nom./Low/Silent operation	dBA	41/40/34/29/21		42/41/34/30/22		44/40/38/35/32		46/43/41/37/33			
Power supply	Phase / Frequency / Voltage			Hz / V									
				1~ / 50 / 220-240									

OUTDOOR UNIT				ARXN25MB		ARXN35MB		ARXN50MB		ARXN60MB		
Dimensions	Unit	HeightxWidthxDepth		mm	550x658x289				753x855x328			
Weight	Unit			kg	31				44			
Compressor	Type			Hermetic swing								
Sound power level	Cooling			dBA	58		60		64		65	
Sound pressure level	Cooling	Nom.		dBA	45		46		51			
	Heating	Nom.		dBA	45		46		51			
Operation range	Cooling	Ambient	Min.~Max.	°CDB	10~46				-10~46			
	Heating	Ambient	Min.~Max.	°CWB	-15~18							
Refrigerant	Type			R-410A								
	GWP			1,975								
Piping connections	Liquid	OD		mm	6.35							
	Gas	OD		mm	9.52				12.70		15.90	
	Piping length	OU - IU	Max.	m	20				30			
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50 / 220-240							



ATXN25-35MB



AP GS02



ARXN25-35MB

Daikin has a worldwide reputation based on 90 years' experience in the successful manufacture of high quality air conditioning equipment for residential, commercial and industrial use and 56 years as a leader in heat pump technology.

The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.



Daikin Europe N.V. participates in the Eurovent Certification programme for Liquid Chilling Packages (LCP), Air handling units (AHU) and Fan coil units (FCU). Check ongoing validity of certificate online: www.eurovent-certification.com or using: www.certiflash.com



Daikin products are distributed by:

FSC

ECPEN14-032